

DC PORTABLE DC

DC130V-500A

500 A · 130 VDC

Battery bank load bank with 1 A resolution from 1 A to 500 A.



TECHNICAL SPECIFICATION

RATING	500 A at 130 VDC
LOAD STEPS	1 A to 500 A
CONTROL POWER	External 1 kW at 230 V, 1 ph, 60 Hz

DIMENSIONS & WEIGHT

LENGTH	WIDTH	HEIGHT	WEIGHT
20"	30"	35"	115 kg

ABOUT THIS LOAD BANK

A high-performance testing system designed to accurately measure the output power and load capacity of battery banks, with real-time data monitoring, intelligent control and advanced safety features.

USED FOR

Batteries

KEY FEATURES

- ✓ 0.5-class accuracy on voltage, current, power and dynamic parameters
- ✓ Emergency stop, overvoltage, short-circuit and temperature protection
- ✓ Touch-screen remote panel and data management software
- ✓ Local, remote and PC-based control
- ✓ Forced-air cooling

Specifications from the manufacturer's datasheet. Confirm availability and configuration with PLS before ordering.

RENT THIS UNIT

Power Line Services — Dammam

+966 55 786 4095

sales@plssa.com

plssa.com

Khalidiyah, Dammam, Kingdom of Saudi Arabia