

DC PORTABLE DC

HDGC3980

300 A · 10–60 VDC

Battery discharge tester for capacity measurement and routine maintenance, with automatic reporting.



TECHNICAL SPECIFICATION

RATING	300 A at 10 VDC to 60 VDC
LOAD STEPS	0 to 300 A
CONTROL POWER	External 5 kW at 230 V, 1 ph, 60 Hz

DIMENSIONS & WEIGHT

Dimensions available on request.

ABOUT THIS LOAD BANK

The HDGC3980 Series Battery Discharge Tester is used for battery discharge testing, capacity measurement and routine maintenance, with real-time monitoring of voltage, current, time and capacity — for telecom, power stations, rail, hydro plants and UPS data centres.

USED FOR

Batteries UPS Data centres

KEY FEATURES

- ✓ 7" HD touchscreen with strong anti-interference
- ✓ Automatic data recording and preset discharge parameters per battery type
- ✓ 3–5 minute rapid capacity estimate with automatic Excel/Word reports
- ✓ Protection against over-current, short-circuit, overheating and reverse polarity, with alarms and auto shutdown
- ✓ Parallel operation for higher discharge currents

Specifications from the manufacturer's datasheet. Confirm availability and configuration with PLS before ordering.

RENT THIS UNIT

Power Line Services — Dammam

+966 55 786 4095

sales@plssa.com

plssa.com

Khalidiyah, Dammam, Kingdom of Saudi Arabia